

KOROK C-Track

KOROK C-Track is available in the following sizes, weights and lengths.

Product ID	Type	Dimensions	Steel Thickness	Colour	Selling Unit Length	Weight Per L/M	Weight Per Unit
PN1159	C Track	60 x 51 x 60mm	1.15mm	Galvanized	3.0m	1.59kg	4.78kg
PN1159P	C Track	60 x 51 x 60mm Pre-punched 400 centers	1.15mm	Galvanized	3.0m	1.59kg	4.78kg
PN1140	C Track	60 x 80 x 60mm	1.15mm	Galvanized	3.6m	1.80kg	6.71kg
PN1140P	C Track	60 x 80 x 60mm Pre-punched 400 centers	1.15mm	Galvanized	3.6m	1.80kg	6.71kg
PN1141	C Track	90 x 80 x 90mm	1.15mm	Galvanized	3.0m	2.42kg	7.27kg
PN1141P	C Track	90 x 80 x 90mm Pre-punched 400 centers	1.15mm	Galvanized	3.0m	2.42kg	7.27kg
PN1147	C Track	120 x 80 x 120mm	1.15mm	Galvanized	2.4m	2.98kg	6.71kg
PN1144	C Track	60 x 80 x 60mm	1.15mm	P/Coated Grade A	3.6m	1.86kg	6.21kg
PN1145	C Track	90 x 80 x 90mm	1.15mm	P/Coated Grade A	3.0m	2.42kg	7.27kg
PN1146	C Track	120 x 80 x 120mm	1.15mm	P/Coated Grade A	2.4m	2.98kg	7.16kg
PN1148	C Track	90 x 80 x 90mm	1.55mm	Galvanized	2.4m	3.24kg	7.77kg
PN1142	C Track	120 x 80 x 120mm	1.55mm	Galvanized	2.4m	3.94kg	9.57kg

All KOROK C-Track is produced in Hamilton by KOROK. KOROK C-Track must be used in KOROK Systems to meet the stated performance of the system and to maintain the systems Warranty.

