

KS2115-13

SPEC. CODE	STC	FRR	WALL THICKNESS*	FRAME	CAVITY	SYSTEM SUMMARY
KS2115-13	56	-/120/60	141mm	Horizontal or vertical 28mm furring channel at 600mm centres on Rondo Betagrip clips BG02	n/a	KOROK® 78mm panel (400 kg/m³) + 1 layer 13mm GIB® Noiseline® one side

*Nominal thickness

KOROK® PANEL

KOROK® 78mm panels are located in KOROK® C-track 60mm high x 80mm wide x 1.15B.M.T. The KOROK® C-track is fixed to the structure at 400mm centres max, and bedded on a bead of KOROK® acrylic fire seal. KOROK® panels must not exceed 6 metres in height.

FRAMING

Horizontal 28mm Furring channel at 600mm maximum centres one side mounted on Rondo Betagrip clips BG02.

Channel must be installed as per manufacturer's instructions.

ACOUSTIC INSULATION

Acoustic insulation must be R1.2 x 50mm thick insulation 12.8kg/m³ or equivalent.

LINING

1 layer of 13mm GIB® Noiseline® or equivalent.

Plasterboard linings are installed to the manufacturer's specification. Joints must be stopped.

SEALANT

Beads of KOROK® acrylic fire seal are required around the perimeter of the KOROK® system.

