

KS2115-20

SPEC. CODE	STC	FRR	WALL THICKNESS*	FRAME	CAVITY	SYSTEM SUMMARY
KS2115-20	51	-/120/60	136mm	45mm x 45mm timber battens at 600 centers vertically or horizontally	n/a	KOROK® 78mm panel (400 kg/m³) + 1 layer 13mm GIB® Standard plasterboard one side

*Nominal thickness

KOROK® PANEL

KOROK® 78mm panels are located in KOROK® C-track 60mm high x 80mm wide x 1.15B.M.T. The KOROK® C-track is fixed to the structure at 400mm centres max, and bedded on a bead of KOROK® acrylic fire seal. KOROK® panels must not exceed 6 metres in height.

FRAMING

45mm x 45mm timber battens at 600 centers vertically or horizontally.

Battens must be installed as per manufacturer's instructions.

ACOUSTIC INSULATION

Acoustic insulation must be R1.0 45mm Mammoth masonry wall blanket or equivalent.

LINING

1 layer of 13mm GIB® Standard Plasterboard or equivalent.

Plasterboard linings are installed to the manufacturer's specification. Joints must be stopped.

SEALANT

Beads of KOROK® acrylic fire seal are required around the perimeter of the KOROK® system.

